



WORKSTAR® MID-RANGE DIESEL

YOUR UNIQUE BUSINESS REQUIRES THE RIGHT TRUCK

Your business and your customers demand that you be ready for anything. That's why we built the International® WorkStar.® It's all about options, offering several possible configurations, such as the 4x2, 4x4, 6x4 or 6x6. The set-back or set-forward axle allows you the flexibility to build the right truck for your application. Throw in the option of the powerful MaxxForce® 9 diesel engine or the standard MaxxForce DT—both with a variety of horsepower and torque options—and you get the truck you need for your company to run at its best.



A NAVISTAR COMPANY

WORKStar.
POWERED BY MAXXFORCE

INTERNATIONAL® WORKSTAR® MID-RANGE DIESEL SPECIFICATIONS

GVW

- ▶ 27,500 – 60,000 lbs.

Models/BBC/BA

- ▶ 7300, 7400, 7500: 107", 32" Set Forward BA, 39.9" Set Back BA

Cab Configurations

- ▶ Day Cab, Extended Cab, Crew Cab

Wheelbase Options

- ▶ 128 – 262"

Axle Configurations

- ▶ 4x2, 4x4, 6x4, 6x6

Rear Axle

Single Rear Axle (4x2)

- ▶ Meritor: 17,000 – 38,000 lbs.
- ▶ Dana Spicer: 17,500 – 30,000 lbs.

Tandem Rear Axle (6x4, 6x6)

- ▶ Meritor: 34,000 – 46,000 lbs.
- ▶ Dana Spicer: 34,000 – 46,000 lbs.

Front Axle

- ▶ Meritor: 10,000 – 22,000 lbs.
- ▶ Dana Spicer: 10,000 – 20,000 lbs.
- ▶ Meritor Front Driving: 10,000 – 22,000 lbs.
- ▶ Fabco Front Driving: 10,000 – 14,600 lbs.

Frames

- ▶ High Strength Low Alloy Steel 80,000 PSI
- ▶ Heat Treated Alloy Steel 120,000 PSI

Front Suspension

- ▶ Spring Parabolic Taper Leaf: 10,000 – 22,000 lbs.
- ▶ Spring Multi-Leaf: 10,000 – 20,000 lbs.

Tires

- ▶ Continental, Michelin, Goodyear

Rear Suspension

- ▶ Spring Single Vari-Rate: 18,500 – 40,000 lbs.
- ▶ Spring Single Air: 20,000 lbs.
- ▶ Tandem Spring: 40,000 – 46,000 lbs.
- ▶ Tandem Air Spring: 40,000 – 46,000 lbs.

Electrical System

- ▶ Diamond Logic® electrical system
- ▶ Alternators: Leece-Neville 12 Volt 120, 160, 185, 220, 320 Amp. Delco Remy 12 Volt 130, 135, 145, 165 Amp. Bosch 12 Volt 160, 165, 200 Amp.
- ▶ Battery Systems: International 12-Volt 1300, 1850, 1950, 2250, 2775 CCA

Exhaust System

- ▶ Single, Horizontal or Vertical, After-treatment Device Frame Mounted Left or Right Side, Back of Cab or Under Cab

Brakes

- ▶ Air Drum Brakes with ABS, Optional Traction Control, Optional Electronic Stability Program with Traction

Steering

- ▶ Single Power
- ▶ Dual Power on front axles 16,000 lbs. and higher

Engines

- ▶ MaxxForce DT: Up to 300 hp, 860 lb.-ft. torque
- ▶ MaxxForce 9: Up to 330 hp, 950 lb.-ft. torque
- ▶ MaxxForce 10: Up to 350 hp, 1150 lb.-ft. torque

Transmissions

- ▶ Eaton-Fuller: 5, 6, 8LL, 9LL, 10, 13 speed manual
- ▶ Eaton: UltraShift 6 speed automated manual
- ▶ Allison: 2000, 3000 Series (HS, EVS, RDS) automatic

Fuel Tank

- ▶ 50 – 80 Gallon, Non-Polished or Polished Aluminum, Mounted Right or Left Side Under Cab

KEY FEATURES

- ▶ Wide-track axles providing maximum maneuverability and up to a 50° wheel cut
- ▶ Cooling system mounted above frame-rails to accommodate front-mounted PTO without notching the radiator—ensuring maximum durability, cooling capacity, and ground clearance in on/off-highway environments
- ▶ Diamond Logic® electrical system's on-board diagnostics monitors all vehicle components to reduce downtime and keep you informed of your vehicle's status
- ▶ Double-sided galvanized steel cab built for quality fit and finish, and long-term protection from corrosion
- ▶ One-piece wrap-around windshield for outstanding visibility
- ▶ Standard air-ride cab provides smooth ride and increases driver comfort
- ▶ Natural gas and hybrid options available



A NAVISTAR COMPANY